### Note on English translation / Hinweise zur englischen Fassung

This is a translation of the technical data sheet valid in Germany.

All stated details and properties are in compliance with the regulations of the German standards and building regulations. They are only applicable for the specified products, system components, application rules, and construction details in connection with the specifications of the respective certificates and approvals.

Knauf Gips KG denies any liability for applications outside of Germany as this requires changes acc. to the respective national standards and building regulations.





K442a.de

Drywall Systems

2012-05

# **Knauf Joint Tape Kurt**

Reinforcement tape for joint filling

### **Product description**

Knauf Joint Tape Kurt is a paper joint tape acc. to DIN EN 13963.

The tape is 50 mm wide, with centered folding seam and consists of white special paper.

### **Order Information**

25 m roll Material no. 00099381 75 m roll Material no. 00099382

### Storage

Store in a dry place.

### Fields of application

Knauf Joint Tape Kurt is used

- as reinforcement tape for the joint filling of gypsum boards and gypsum fiber boards,
- as reinforcement tape for the filling of joints between prefab concrete units,
- as reinforcement tape for repairing cracks of interior plaster surfaces.

### **Properties**

- High strengths
- Easy application
- No hygroexpansion
- Can be folded for internal corners

# K442a.de Knauf Joint Tape Kurt

Reinforcement tape for joint filling



### Ausführung

### Filling of gypsum board joints

(HRAK, AK, AFK, SK)

Apply filler, e.g. Knauf Fugenfüller Leicht, on joints uniformly, approx. 80 mm wide, and 1 mm thick. Embed Knauf Joint Tape Kurt immediately afterwards by applying the tape on the joint filler (outside of roll towards joint), and push it firmly into the filler with a drywall knife or trowel. Use excess material to cover the tape. Apply one or more coats of joint filler for smoothing, depending on the surface quality category required.

If Knauf Fugenfüller Leicht is used as joint filler, use Knauf Joint Tape Kurt both for the filling of cut-edge joints (e.g. front edge joints) AND longitudinal joints.

If Knauf TRIAS, Uniflott or Uniflott impregnated are used, the application of Knauf Joint Tape

Kort is recommended for the filling of cut-edge joints (e. g. front edge joints).

### Filling of prefab concrete joints

300 mm wide.

Fill joints of prefab concrete units with Knauf Multi-Finish (in the case of machine application use Knauf Multi-Finish M), and apply a coat of approx. 1 mm thickness around the joint. Apply Knauf Joint Tape Kurt, and push it firmly into the filler bed using a drywall knife or trowel.

After drying, apply a filler coat, approx. 200 to

## Repairing cracks

Wait until no more crack development can be expected. The surface should be sturdy (even if the surface is moist), substantially strong, dry, and free of dust. Remove unstable coats, paint etc. if necessary. Prime with Knauf Tiefengrund. After drying, glue Knauf Joint Tape Kurt centered on the crack using PVA glue, and push it firmly onto the surface. After drying, apply a filler coat with Knauf Readygips or Knauf Multi-Finish.

Consumption of material				
Knauf Joint Tape Kurt		Consumption in m/m² for the joint filling of gypsum boards		
Board width	Joint	<b>Ceiling</b> (10 x 10 m)	Partition (4 x 2.75 m)	Dry lining / furring / installation shaft wall (4 x 2.75 m or 4 x 2.6 m for dry lining)
1250 mm	Long edge joint Front edge joint	ca. 0.75 ca. 0.45	ca. 1.5 as required (depen	ca. 0.75 ding on number of horizontal board joints)
625 mm	Long edge joint Front edge joint	ca. 1.5 ca. 0.45	ca. 3 as required (depen	ca. 1.5 ding on number of horizontal board joints)

### **Knauf Direct**

Technical Advisory Service:

Phone.: +49 9001 31-1000 \*

Fax: +49 1805 31-4000 \*\*

www.knauf.de

Knauf Gips KG Am Bahnhof 7, 97346 Iphofen, Germany

- \* Call rates to Knauf Direct from within the German landline network: 0.39 € per Min., Callers whose phone numbers are not registered in the Knauf address database, e. g. private builders or non-patrons are charged 1.69 €/Min. Calls from mobile phones may differ and will be charged acc. to net provider and call rate.
- \*\* Fax: 0.14 €/Min. within the German landline network

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. The stated information represents current state-of-the-art Knauf technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Knauf Gips KG, Am Bahnhof 7, 97346 lphofen, Germany.

Delivery via professional building material distributors only, in accordance with our current business, delivery and payment terms.

The stated constructional and structural design specifications and characteristics of building physics of Knauf systems can only be achieved with the exclusive use of Knauf system components, or other products expressly recommended by Knauf.